

| | Monster | Monster+ |
|---|---|--|
| ENGINE | | |
| TYPE | Testatretta 11°, V2 - 90°, 4 valves per cylinder, desmodromic valvetrain, liquid cooled | Testatretta 11°, V2 - 90°, 4 valves per cylinder, desmodromic valvetrain, liquid cooled |
| DISPLACEMENT | 937 cc (57 cu in) | 937 cc (57 cu in) |
| BORE X STROKE | 94 mm x 67.5 mm | 94 mm x 67.5 mm |
| COMPRESSION RATIO | 13.3:1 | 13.3:1 |
| POWER | 111 hp (82 kW) @ 9,250 rpm | 111 hp (82 kW) @ 9,250 rpm |
| TORQUE | 9.5 kgm (93 Nm, 69 lb ft) @ 6,500 rpm | 9.5 kgm (93 Nm, 69 lb ft) @ 6,500 rpm |
| FUEL INJECTION | Electronic fuel injection system, Ø 53 mm throttle bodies with Ride-by-Wire system | Electronic fuel injection system, Ø 53 mm throttle bodies with Ride-by-Wire system |
| EXHAUST | Pre-muffler and twin muffler, catalytic converter and 2 lambda probes | Pre-muffler and twin muffler, catalytic converter and 2 lambda probes |
| TRANSMISSION | | |
| GEARBOX | 6 speed | 6 speed |
| PRIMARY DRIVE | Straight cut gears, ratio 1.85:1 | Straight cut gears, ratio 1.85:1 |
| RATIO | 1=37/15, 2=30/17, 3=28/20, 4=26/22, 5=24/23, 6=23/24 | 1=37/15, 2=30/17, 3=28/20, 4=26/22, 5=24/23, 6=23/24 |
| FINAL DRIVE | Chain, front sprocket z15, rear sprocket z43 | Chain, front sprocket z15, rear sprocket z43 |
| CLUTCH | Slipper and self-servo multiplate wet clutch with hydraulic control | Slipper and self-servo multiplate wet clutch with hydraulic control |
| CHASSIS | | |
| FRAME | Aluminum alloy Front Frame | Aluminum alloy Front Frame |
| FRONT SUSPENSION | Ø 43 mm usd fork | Ø 43 mm usd fork |
| FRONT WHEEL | Light alloy cast, 3.5" x 17" | Light alloy cast, 3.5" x 17" |
| FRONT TYRE | Pirelli Diablo Rosso III 120/70 ZR17 | Pirelli Diablo Rosso III 120/70 ZR17 |
| REAR SUSPENSION | Progressive linkage, preload adjustable monoshock, aluminium double-sided swingarm | Progressive linkage, preload adjustable monoshock, aluminium double-sided swingarm |
| REAR WHEEL | Light alloy cast, 5.5" x 17" | Light alloy cast, 5.5" x 17" |
| REAR TYRE | Pirelli Diablo Rosso III 180/55 ZR17 | Pirelli Diablo Rosso III 180/55 ZR17 |
| WHEEL TRAVEL (FRONT/REAR) | 130 mm / 140 mm (5.1 in / 5.5 in) | 130 mm / 140 mm (5.1 in / 5.5 in) |
| FRONT BRAKE | 2 x Ø 320 mm semi-floating discs, radially mounted Brembo M4.32 monobloc 4-piston callipers, radial master cylinder, Cornering ABS | 2 x Ø 320 mm semi-floating discs, radially mounted Brembo M4.32 monobloc 4-piston callipers, radial master cylinder, Cornering ABS |
| REAR BRAKE | Ø 245 mm disc, Brembo 2-piston floating calliper, Cornering ABS | Ø 245 mm disc, Brembo 2-piston floating calliper, Cornering ABS |
| INSTRUMENTATION | 4.3" TFT colour display | 4.3" TFT colour display |
| DIMENSIONS AND WEIGHTS | | |
| DRY WEIGHT | 166 kg (366 lb) | 166 kg (366 lb) |
| KERB WEIGHT* | 188 kg (414 lb) | 188 kg (414 lb) |
| SEAT HEIGHT | 820 mm (32.3 in) 800 mm (31.5 in) (accessory low seat) 775 mm (30.5 in) (accessory low seat + low suspension kit) | 820 mm (32.3 in) 800 mm (31.5 in) (accessory low seat) 775 mm (30.5 in) (accessory low seat + low suspension kit) |
| WHEELBASE | 1,474 mm (58.0 in) | 1,474 mm (58.0 in) |
| RAKE | 24° | 24° |
| TRAIL | 93 mm (3.7 in) | 93 mm (3.7 in) |
| FUEL TANK CAPACITY | 14 l (3.7 US gal) | 14 l (3.7 US gal) |
| NUMBER OF SEATS | 2 | 2 |
| EQUIPMENT | | |
| SAFETY EQUIPMENT | Riding Modes, Power Modes, Cornering ABS, Ducati Traction Control, Ducati Wheelie Control, Daytime Running Light | Riding Modes, Power Modes, Cornering ABS, Ducati Traction Control, Ducati Wheelie Control, Daytime Running Light |
| STANDARD EQUIPMENT | Ducati Quick Shift, Ducati Power Launch, 4.3" TFT colour display, Full LED headlight and lighting system, Dynamic turn indicators, USB power socket | Ducati Quick Shift, Ducati Power Launch, 4.3" TFT colour display, Full LED headlight and lighting system, Dynamic turn indicators, USB power socket, Flyscreen, Passenger seat cover |
| READY FOR | Ducati Multimedia System, Heated grips | Ducati Multimedia System, Heated grips |
| WARRANTY AND MAINTENANCE | | |
| WARRANTY | 24 months, unlimited mileage | 24 months, unlimited mileage |
| MAINTENANCE SERVICE INTERVALS | 15,000 km (9,000 miles) / 12 months | 15,000 km (9,000 miles) / 12 months |
| DESMO SERVICE | 30,000 km (18,000 miles) | 30,000 km (18,000 miles) |
| EMISSIONS AND CONSUMPTION (Only for countries where Euro 5 standard applies) | | |
| STANDARD | Euro 5 | Euro 5 |
| CO2 EMISSIONS | n/a | n/a |
| CONSUMPTION | n/a | n/a |

*Kerb weights indicate total bike weight with all operating consumable liquids and a fuel tank filled to 90% of capacity (as per EU Regulation

** Not available in Canada, China, Japan